

PolySOL Roll-up Film 180

■ satin 3515 - 180 µm

PolySOL Roll-up Film is a satin finished, waterfast polyester film for solvent inks. Due to the grey backside the opacity reaches more than 99.9%. It is perfectly suited for free-standing roll-up applications. The excellent flatness allows this media to be used for a wide range of signage, advertisement and POS applications. The innovative coating and the high whiteness lead to a short drying time and a wide colour gamut with Eco- Mild- and True-Solvent inks. The product is suitable for hot and cold lamination.

Applications

- Indoor Signs
- Indoor Short-term Promotions
- Pop-up Displays
- Outdoor Signage

Advantages

- High opacity
- Fast drying time
- Tear resistant polyester
- Waterfast prints
- High color brilliance

PolySOL Roll-up Film 180

■ satin 3515 - 180 µm

List of Printers

Printer	Ink	Quality
Hewlett Packard DJ 8000S / 9000S / 10000S	Eco Solvent	Excellent
Hewlett Packard DJ L25500 Latex ink	IR Curing / Latex Ink	Excellent
Epson Stylus Pro GS6000 UltraChrome GS	Eco Solvent	Excellent
Roland SolJet SJ540 / SC540 SJ 740 / SC740	Eco Solvent	Excellent
Roland VersaCAMM SP-300i / SP-540i	Eco Solvent	Good
Roland VersaCAMM VP-300i / VP-540i	Eco Solvent	Good
Mimaki JV-3 160S, 250	Solvent Ink	Good
Mimaki JV 5-130 / -160	Eco Solvent	Good
Mutoh Toucan	Solvent Ink	Good
Mutoh Rockhopper II 50", 64", 87"	Eco Solvent	Good
Mutoh ValueJet 1204 / 1304 /1614	Eco Solvent	Good
Océ CS6060	Eco Solvent	Good

Last update: 20.05.2010

PolySOL Roll-up Film 180

■ satin 3515 - 180 µm

Physical Properties

Test Conditions	23°C / 50% R.F:	
Weight g/m ²	235	ISO 536
Thickness µm	185	ISO 534
Opacity	>99%	ISO 2471
Gloss 60°	16	ISO 2813

Conditions of Use and Stocking

The converting and storage should take place in a climate from 35 to 65% to relative humidity at a temperature from 10° to 30° C. Keep the product in the original packaging (cardboard box and PE bag). It is always recommended that cotton gloves be used when handling InkJet coated materials to avoid fingerprints.

The data provided in this product data sheet are values for orientation only.

Before using our print media please check their suitability for your printer and for your intended application. We do not take any liability for failures or damages resulting from technically modified printing inks and/or printers as technical specifications are subject to change.

16.02.2006